

# Model: COMPACT line

## Order number: 29-200977-031

Correct use: Passive storage



classical door technology (door handle) for the storage of flammable liquids type testing by MPA/TÜV SÜD according to DIN EN 14470-1, DIN EN 16121 and DIN EN 16122, EK5/AK4 09-10:2009 and AfPS GS 2014: 01 PAK mark of approval: GS/CE mark, high quality mark of approval by TÜV SÜD construction and colour:

- outer carcass sheet steel, RAL 7035
- doors sheet steel, RAL 1018
- inner carcass of decor panels, RAL 7035
- fittings and features:
- doors close automatically in case of fire
- doors remain open in every position
- cylinder lock for safe access
- bottom tray sheet steel, RAL 7035
- hot-dip galvanised grating
- exhaust air connection socket on the cabinet roof
- visual inspection of the ventilation opening
- earthing connection on the cabinet roof
- interior fittings conductively connected with carcass
- adjustable foot for level adjustment
- set-back base,

Category: Type 90 - flammable liquids Model size: LL, Model type: STANDARD (storage shelves), Outer height [mm]: 2.085, Outer width [mm]: 894, Outer depth [mm]: 747, Gross weight [kg]: 442,00, Net weight [kg]: 442,00, Equipment package: for 200 liter drum, Number of storage levels: 1, Number of storage areas per storage level: 1, Door operation: classical technology, Door technology: wing door technology,