

Model:
Order number: 29-201266-030

Correct use: Passive storage



Pneumatical door technology (foot pedal). For the storage of flammable liquids. Type testing by MPA/TÜV SÜD according to DIN EN 14470-1, DIN EN 16121 and DIN EN 16122, EK5/AK4 21-01:2021 and AfPS GS 2019:01 PAK Mark of approval: GS/CE mark, high quality mark of approval by TÜV SÜD Construction and colour:

- Outer carcass sheet steel, RAL 7035
- Doors sheet steel, RAL 1018
- Inner carcass of decor panels, RAL 7035 Fittings and features:
- Doors close automatically
- Cylinder lock for safe access
- Bottom tray sheet steel, RAL 7035
- 4 storage shelves, RAL 7035
- Exhaust air connection socket on the cabinet roof
- Visual inspection of the ventilation opening
- Earthing connection on the cabinet roof
- Interior fittings conductively connected with carcass
- Adjustable foot for level adjustment
- Set-back base, RAL 7015 Further technical information: www.dueperthal.com

Category:	Type 90 - flammable liquids
Model size	XL

Model type	STANDARD (storage shelves)
Outer width [mm]:	1.194
Outer depth [mm]:	597
Outer height [mm]:	2.077
Net weight [kg]:	510,00
Number of storage levels	4
Number of storage areas per storage level	1
Door operation	classical technology
Door technology	folding door technology