

Model: HSC UTS ERGO LINE

Order number: 39-061167-015

Correct use: Combination (passive storage)



Classical door technology (door handle). For the combined storage of acids, lye and flammable liquids. Type-tested by MPA/TÜV SÜD according to DIN EN 14470-1, DIN EN 16121, and DIN EN 16122 Marks of approval: GS/CE mark, High Quality mark of approval awarded by TÜV SÜD
Construction and colour:

- Outer carcass sheet steel, RAL 7035
- Doors sheet steel, RAL 9002 (left side) & RAL 1018 (right side)
- Inner carcass left polypropylene (white)
- Inner carcass decor panels, RAL 7035
- base with slots for floor extraction, RAL 7015 Fittings and features left side (acids and lye):
- Extendable PP tray with arrest system to prevent unintentional pulling out.
- Exhaust air connection socket on the rear of the cabinet Fittings and features right side (type 90):
- Door remains open in any position
- Cylinder lock for access security
- Door closes automatically in case of fire
- Bottom tray powder-coated
- Perforated sheet insert powder-coated
- Exhaust air connection socket and earthing connection on the rear of the cabinet (outside). Earthing connection conductively connected with the carcass.
- Interior fittings in RAL 7035 (light grey), conductively connected with the carcass
- Visual inspection of the venting cut-off flaps Further technical information:
www.dueperthal.com

Category: Type 90 - combined storage Model size: LD, Outer height [mm]: 631, Outer width [mm]: 1.100, Outer depth [mm]: 595, Gross weight [kg]: 180,00, Net weight [kg]: 180,00, Number of storage levels: 1, Number of storage areas per storage level: 2, Door operation: classical technology, Door technology: wing door technology,