

**Model: SUPPLY LINE**  
**Order number: 49-200977-031**

Correct use: Supply (active storage)



Classical door technology (door handle). For the active storage of flammable liquids. type testing by MPA/TÜV SÜD according to DIN EN 14470-1, DIN EN 14727, EK5/AK4 21-01:2021 and AfPS GS 2019: 01 PAK. Classification of ex-zones according to DIN EN 60079-10. Mark of approval: GS/CE mark, high quality mark of approval by TÜV SÜD. Construction and colour:

- Outer carcass sheet steel, ELGR conductive
- Doors sheet steel, ELBL conductive
- Inner carcass sheet steel, ELGR conductive ELGR >> similar to RAL 7035 ELBL >> similar to RAL 5010 Fittings and features:
- doors close automatically in case of fire
- doors remain open in any position
- cylinder lock for safe access
- bottom tray sheet steel, ELGR conductive
- hot-dip galvanised grating
- exhaust air connection socket on the cabinet roof
- visual inspection of the ventilation opening
- earthing connection on the cabinet roof
- interior fittings conductively connected with carcass
- adjustable feet for level adjustment
- set-back base, RAL 7015
- exhaust air monitoring unit with ventilator Further technical information:  
[www.dueperthal.com](http://www.dueperthal.com)

Category:	Type 90 - flammable liquids
Model size	LL

Outer width [mm]:	894
Outer depth [mm]:	747
Outer height [mm]:	2.085
Net weight [kg]:	480,00
Equipment package	for 200 litre drum, incl. exhaust air monitoring, ventilator
Number of storage levels	1
Number of storage areas per storage level	1
Door operation	classical technology
Door technology	wing door technology