

Model: DISPOSAL LINE

Order number: 59-200667-035

Correct use: Disposal (active storage)



Classical door technology (door handle), door hinge right For the active storage of flammable liquids. type testing by MPA/TÜV SÜD according to DIN EN 14470-1, DIN EN 14727, EK5/AK4 21-01:2021 and AfPS GS 2019: 01 PAK. Classification of ex-zones according to DIN EN 60079-10. Mark of approval: GS/CE mark, high quality mark of approval by TÜV SÜD. Construction and colour:

- Outer carcass sheet steel, ELGR conductive
- Doors sheet steel, ELBL conductive
- Inner carcass sheet steel, ELGR conductive ELGR >> similar to RAL 7035 ELBL >> similar to RAL 5010 Fittings and features:
- doors close automatically in case of fire
- doors remain open in any position
- cylinder lock for safe access
- bottom tray sheet steel, ELGR conductive
- hot-dip galvanised grating
- 1 safety funnel with lid
- 2 canisters, 30 l each,
- monitoring filling level
- exhaust air connection on the cabinet top
- visual inspection of the ventilation opening
- earthing connection on the cabinet top
- interior fittings grounded to carcass
- adjustable feet for level adjustment
- set-back base, RAL 7015

Further technical information: www.dueperthal.com

Category: Type 90 - flammable liquids Model size: M, Model type: C (tall cabinet), Outer height [mm]: 2.085, Outer width [mm]: 594, Outer depth [mm]: 612, Gross weight [kg]: 350,00, Net weight [kg]: 350,00, Equipment package: for 30 litres, Number of storage levels: 1, Number of storage areas per storage level: 1, Door operation: classical technology, Door technology: wing door technology,