

Model: BATTERY LINE

Order number: 69-200667-030

Correct use: Storage of batteries



Classical door technology (door handle), door hinge right For the storage of lithium-ion batteries
Type-tested by MPA/ TÜV SÜD according to DIN EN 14470-1, DIN EN 16121, DIN EN 16122, and DIN 31000 Loss prevention in terms of VdS 3103 Mark of approval: Safety tested and CE mark
Construction and colour:

- Outer carcass sheet steel, RAL 7035
- Doors sheet steel, PANTONE 389 C
- Inner carcass decor panels, RAL 7035 Fittings and features:
- Doors remain open in any position
- Doors close automatically in case of fire
- Cylinder locks for access security
- Backdraftlock after inside fire
- bottom tray sheet steel, RAL 7035
- 4 storage levels sheet steel, RAL 7035
- 1 storage area per storage level
- exhaust air connection on the cabinet roof
- visual inspection of the ventilation opening
- earthing connection on the cabinet roof
- interior fittings grounded to carcass
- adjustable feet for level adjustment
- set-back base, RAL 7015 more technical information: www.dueperthal.com

Category: Type 90 - lithium ion batteries Model size: M, Model type: STANDARD (storage shelves),
Outer height [mm]: 2.045, Outer width [mm]: 594, Outer depth [mm]: 612, Gross weight [kg]:
310,00, Net weight [kg]: 310,00, Supply voltage: no charging system, Equipment package: without

signal transmission, Number of storage levels: 4, Number of storage areas per storage level: 1,
Door operation: classical technology, Door technology: wing door technology,